



# ASTUN Y HSA

# ABSORBEDOR DE ENERGÍA

FICHA TÉCNICA

Producto



Descripción

- Absorbedor de energía con doble cuerda de poliéster.
- Diseñado para soportar caídas y reducir el impacto de caída por debajo de 6kN.
- Chip NFC Ready: Chip incorporado para trazabilidad de producto, estado y revisión.

# CARACTERÍSTICAS

Características generales	Norma	EN 355   EN 362   TEST 140kg   VG11.063			
	Longitud	140cm		180cm	
	Peso	1640g		1720g	
	Capacidad de uso	140kg			
	Diámetro cuerda	12mm			
	Tipo de cuerda/cinta	Bifurcado			
	Vida útil	10 años de uso + 2 años de almacenamiento			
Materiales generales	Componente	Material			
	Absorbedor	Poliéster			
	Cuerda	Poliéster			
	Conectores	Aluminio			
Conectores	Componente	Unidades	Material	Cierre	Abertura
	Silverlight 1135	1	Aluminio	Screw-lock	22mm
	Silverlight 984	2	Aluminio	Due-lock	60mm

# ENERGY ABSORBER

Product



Description

- Energy absorber with double polyester rope.
- Designed to withstand falls and reduce fall impact below 6kN.
- NFC Ready Chip: Built-in chip for product traceability, status and revision.

## CHARACTERISTICS

General characteristics	Norma	EN 355   EN 362   TEST 140kg   VG11.063	
	Length	140cm	180cm
	Weight	1640g	1720g
	Capacity to use	140kg	
	Diameter of rope	12mm	
	Type of rope/strap	Bifurcated	
	Shelf life	10 years of use + 2 years of storage	

General materials	Component	Material
	Absorber	Polyester
	Rope	Polyester
	Connectors	Aluminium

Connectors	Component	Units	Material	Closing	Opening
	Silverlight 1135	1	Aluminium	Screw-lock	22mm
	Silverlight 984	2	Aluminium	Due-lock	60mm